

PRATIK

ONE COMPONENT POOL PAINT



Product Description:

Boysat Pratik is a hybrid resin-based, single-component, ready-to-use paint. This product provides strong adhesion to surfaces, does not crack or peel, and is flexible and highly covering. It is resistant to adverse weather conditions, unaffected by mild pool chemicals, withstands water pressure, and is insoluble in water. It offers excellent waterproofing on surfaces constantly exposed to water. It is an easy-to-clean and washable decorative insulation coating.

GENERAL SPECIFICATIONS




- ✓ Waterproofing: Provides a strong waterproof barrier.
- ✓ Flexibility: Adapts to structural movements, does not crack or peel.
- ✓ Protection: Resistant to UV rays, temperature changes, mild pool chemicals, and sunlight.
- ✓ Easy Application: Can be easily applied with a brush or finger roller.
- ✓ Durability: Offers high durability and long-lasting insulation.
- ✓ Pressure Resistance: Withstands water pressure.
- ✓ Color Options: Available in transparent, pool blue, or white.



EXTENSIVE APPLICATION RANGE

- All types of decorative, swimming, and agricultural irrigation pools
- Fish farming pools
- Concrete water tanks (except for drinking water tanks)
- Ponds, small canals
- Wet floors of buildings (ceramic tiles, marble)
- Concrete, OSB, particleboard, asbestos cement, and metal roofs
- Roof gutters



TECHNICAL SPECIFICATIONS

- **Application Instructions:** The surface to be applied must be free from dirt, dust, oil, and any loose residues, and it should be clean and dry. To enhance the adhesion of the surface, you can apply a primer using cellulose thinner. Pratik Pool Paint is ready to use and does not require any additional additives. After mixing with a mixer for 3 minutes, apply it to the surface in two coats using a finger roller or brush. The waiting time between coats is 6 hours. Ensure the application is done at temperatures between +5°C and +35°C.
- **Consumption:** 0.5 kg/m² for two coats
- **Color:** Transparent, Blue, White
- **Storage Conditions:** Store in a dry and cool environment, in its original unopened packaging.
- **Shelf Life:** 12 months
- **Packaging Type:** 2, 2.5 kg metal bucket