

S-CIM 2K

CEMENT BASED TWO COMPONENT WATERPROOF COATING



Product Description:

S-CIM 2K is a dual-component, fully elastic water insulation coating synchronized with silicone emulsion and thermal microspheres, reinforced with cementitious fillers. It stands out with its superior adhesion properties and high resistance to water, moisture, and sunlight. It offers unparalleled coating performance, covering 1 m² with a single coat using 0.500 grams.


GENERAL SPECIFICATIONS



- ✓ Waterproofing: Provides a strong waterproof barrier.
- ✓ Flexibility: Adapts to structural movements without cracking or peeling.
- ✓ Protection: Resistant to UV rays, snow, ice, and sun.
- ✓ Easy Application: Can be easily applied with a brush or roller.
- ✓ Color Options: Gray
- ✓ Dual-Component Structure: Its two-component structure ensures maximum performance and long-lasting insulation.

EXTENSIVE APPLICATION RANGE

- **Roofs:** Terrace concrete roofs, gutters, parapet walls, chimneys, tiles, bituminous/slate membranes, shingles
- **Buildings:** Foundation curtain walls, blind facades
- **Wet Areas:** Bathrooms, kitchens, balconies, and all wet surfaces (before and after ceramic, tile, marble application)
- **Pools and Water Tanks:** Swimming pools, large-capacity water tanks, water reservoirs



TECHNICAL SPECIFICATIONS

- **Application Instructions:** The surface to be applied must be free of dirt, dust, oil, and any loose residues, and it should be clean and dry. To enhance the adhesion of the surface, mix the concentrated primer provided with the product with 4 kg of water and apply it to the surface using a roller. Empty the powder and liquid components of S-Çim 2K into a bucket. Then, mix for a few minutes using a drill until the product is ready for use. Apply the product to the surface in two coats using a roller. After application, store the product in an airtight manner to prevent it from hardening. The waiting time between coats is 24 hours. Ensure the application is done at temperatures between +5°C and +35°C.
- **Consumption:** 0.8 kg / m² (double coat)
- **Color:** Gray
- **Storage Conditions:** Store in a dry and cool environment, in its original, unopened packaging.
- **Shelf Life:** 12 months
- **Packaging Type:** 15 kg plastic bucket