

IZO WHITE GLASS


SOLVENT BASED WATERPROOF COATING



Product Description

Izo White Glass forms a strong, walkable, waterproof coating on the applied surface. Thanks to its solvent-based special resin, it becomes a long-lasting coating. It is highly resistant to UV rays and seasonal conditions. Being white in color, it helps reflect sunlight in summer, keeping buildings cool, especially in hot weather.

GENERAL SPECIFICATIONS



- ✓ **Waterproofing:** Provides a strong waterproof barrier.
- ✓ **Thermal Insulation:** Reduces heat absorption, helping keep interiors cooler in summer.
- ✓ **Flexibility:** Adapts to structural movements, does not crack or peel.
- ✓ **Protection:** Resistant to UV rays, temperature changes, snow, ice, and sunlight.
- ✓ **Easy Application:** Can be easily applied with a brush, roller, or spray.
- ✓ **Durability:** Offers high durability and long-lasting insulation.

EXTENSIVE APPLICATION RANGE



- **Roofs:** Terrace concrete roofs, gutters, parapet walls, chimneys, tiles, bituminous/ slate membranes, shingles
- **Wet Areas:** Bathrooms, kitchens, balconies, and all wet floors (before and after ceramic, tile, marble)
- **Industrial Facilities:** Factories, warehouses, industrial sites, poultry houses, animal shelters (provides sun reflection and waterproofing)
- **Other:** Cement board, OSB, particleboard, asbestos sheets (eternit), corrugated/trapezoidal metal sheets

TECHNICAL SPECIFICATIONS

- **Application Instructions:** The surface to be applied must be free from dirt, dust, oil, and any loose residues, and it should be clean and dry. To enhance the adhesion of the surface, you can prime it with cellulose thinner. Izo White Glass is ready to use and does not require any additional additives. After mixing with a mixer for 3 minutes, apply it to the surface in two coats using a roller, brush, or spray. The waiting time between coats is 6 hours. Ensure the application is done at temperatures between +5°C and +35°C.
- **Consumption:** 0.5 kg/m² for two coats
- **Color:** White
- **Storage Conditions:** Store in a dry and cool environment, in its original unopened packaging.
- **Shelf Life:** 12 months
- **Packaging Type:** 1, 2.5, 5 kg metal bucket